

PRODUCT SPEC SHEET

ZEBRA RUGGED TABLETS:
XSLATE B10



ZEBRA
CAPTURE
YOUR EDGE

Zebra XSLATE B10 Rugged Tablet

Product Specifications



DURABILITY	
Drop Test	MIL-STD-810G - 5' drop tested onto plywood over concrete
Hazardous Environment	CID2 (Class 1 Division 2) and ATEX
Ingress	IP65
Internal	Magnesium-alloy internal frame
External	Durable corner bumpers
SYSTEM FEATURES	
Operating System	<ul style="list-style-type: none">• Windows® 10 Pro 64-bit• Windows® 8.1 Pro 64-bit*• Windows® 7 Professional 64-bit** available thru Windows 10 downgrade
Processor	<ul style="list-style-type: none">• Intel® Core™ i5-5350U Processor 1.8 GHz (2.9 GHz Turbo) with vPro™ Technology
Memory	<ul style="list-style-type: none">• 8 GB DDR3L 1600
Storage Options	<ul style="list-style-type: none">• Standard 128 GB SSD• Upgrade to 256 GB or 512 GB
Display	<ul style="list-style-type: none">• 10.1" WXGA (1366 x 768) Rugged IPS LED Backlit Display• 500 NITs Direct Bonded Screen• 178° Viewing Cone (89° Off-Axis)• Contrast Ratio: 800:1; Aspect Ratio: 16:9• Ambient Light Sensor (ALS)• 10-Finger Capacitive Touch Input with Glove and Wet Modes• Pen Input based on Wacom Technology
Graphics	<ul style="list-style-type: none">• Intel® Integrated HD 6000 Graphics
Camera	<ul style="list-style-type: none">• Integrated rear 8 megapixel camera with flash• Integrated Front 1080P FHD Webcam
Integrated Communications	<ul style="list-style-type: none">• Wireless LAN: 802.11ac• Broadband: 4G LTE (Optional)• GPS: Integrated, 2.0m Accurate Satellite• Bluetooth® 4.0• LAN: 10/100/1000 Gigabit Ethernet (RJ-45)
Ports	<ul style="list-style-type: none">• Docking connector• (2) USB 3.0 ports• USB type C port (USB 2.0, USB 3.0, Display Port out)• RJ-45 ethernet port• 3.5 mm audio output (stereo out, mono in)• Dual Nano SIM (4FF)• Micro-SDXC

Integrated Options	<ul style="list-style-type: none">• DC Power• 2 x USB 3.0 Ports• Micro SDXC• Micro HDMI-out• Micro SIM Card Reader• RS232 True Serial Ready Port• Stereo Headphones/Mic Mini-Jack, Smart Phone Headphone Compatible• HDMI Input (Optional)
Battery Life & Power	<ul style="list-style-type: none">• Up to 8 Hour Battery Life (5300 mAh, 39.2 Whr, Single Battery)• Up to 20 Hour Battery Life (8000 mAh, 59.2 Whr, Dual Battery)• Hot Swappable External Battery• Input Voltage: 19V with AC Adapter• Supports 12~20V Input DC on Tablet
Dimensions / Weight	<ul style="list-style-type: none">• 11.05" (28.1 cm) x 7.07" (18.0 cm) x 0.86" (2.2 cm) (W x H x D)• Starting at 2.4 lbs (1.09 kg)
Security	<ul style="list-style-type: none">• Integrated Trusted Platform Module - TPM 2.0• Integrated Fingerprint Scanner• Kensington® Cable Lock Slot (Optional when Using Top Handle)• CAC Reader Module (Optional)
Audio	<ul style="list-style-type: none">• Integrated Speaker and Dual Microphones
Status Indicators	<ul style="list-style-type: none">• Power/Battery Status, Camera Active, HDD Activity
SOFTWARE	
Software	<ul style="list-style-type: none">• xCapture Pro• Panel Control Center• Bios Setup Utility• Touch Mode Switcher (Wet and Glove touch modes)• Sierra Wireless Skylight• Validity Finger Print Manager App• Ublox u-Center• Wacom Pen App• Screen rotate• PC info

PRODUCT SPEC SHEET

ZEBRA RUGGED TABLETS:

XSLATE B10

XSLATE B10 Tablet Specifications (continued)

WARRANTY		ACCESSORIES	
Warranty Information	<ul style="list-style-type: none">• 3 year standard coverage included• Extended Warranty & xDefend Programs available.	Docking	<ul style="list-style-type: none">• xDock G2 IP55 Water and Dust-Resistant Vehicle Dock (12V compatible)• G2 Office Productivity Dock• 2-bay and 6-bay Battery Charging Stands
TESTING AND STANDARDS		Other Accessories	<ul style="list-style-type: none">• Handle/Shoulder Strap with Pen and Tether• Handstrap• Kickstand• Companion Keyboard• True Serial Cable• Armortech Screen Protector• External Battery Brackets, External Battery• 12-16V Input, 19V Output DC-DC Converter (Cigarette Lighter Adapter)• 12-32V Input, 19V Output DC-DC Converter (Heavy Duty Cigarette Lighter Adapter)• 18 - 60V Input, 13.8 V Output DC - DC Converter, Direct Wire
Standards	<ul style="list-style-type: none">• Tested to: MIL-STD-461F• Immunity: CISPR 24, EN55024 (US, CAN, EU)• Emissions: EN55022, CISPR 22, CFR47 Part 15, Subpart B, ICES-003 for Class B (US, CAN, EU), CEC, Regulatory Bulletin No. 110915.02B (BCS), ERP Directive• Safety: CB Scheme, IEC 60950 (US, CAN, EU),• Hazardous Locations: ANSI/ISA 12.12.01 Class I Div 2, A, B, C, D (US, CAN), ATEX		
IEC Ingress Testing	<ul style="list-style-type: none">• IEC (60529) Ingress Tested to IP65 Standard		
Rugged & Environmental	<ul style="list-style-type: none">• Tested to MIL-STD-810G Standards• Operating Temperature: -34 °C to 60 °C / -30 °F to 140 °F• Cold Start: -20 °C / -4 °F• Storage Temperature: -30 °C to 70 °C / -22 °F to 158 °F• Transit Drop - Operating: 5' (1.52 M) Drop Direct to Plywood over Concrete while System is Operating, 26 Drops• Vibration: Minimum Integrity Non-operating, US Highway Truck and Composite Wheel Operating• Shock: Functional (20G Operating, 40G Non-Operating)• Humidity: 23 °C to 60 °C / 73 °F to 140 °F, 95% Non-Condensing, 10 Days• Natural Cycle Humidity: Fig 507.5-6, Non Hazardous B3 Class, 30 Days• Water Proofness: Fig 506.5, 140L/hr, per sq/m, 15 Minutes• Wind Driven Rain: Fig 506.5, 40 MPH Wind, 30 Minutes Per Side• Blowing Sand: 20M/S, rate 1.1g/m3 (+/- .3g) at High Temperature of 60 °C• Blowing Dust: Velocity 8.9m/s Dust Concentration 3.9 g/m3 at High Temperature of 60 °C• Temperature Shock: -30 °C to 70 °C / -22 °F to 158 °F within 5 Minutes• Explosive Atmosphere: Method 511.5, @60 °C, 20,000ft, 10,000ft, and 5,000ft• Contamination by Fluids: 50/50 Solution of Water and Bleach, 50/50 Solution of Water and Hydrogen Peroxide, Diesel Fuel, Mineral Based Oil, Lysol Disinfectant, Denatured Alcohol, Isopropyl Alcohol• Altitude: 40,000 Ft (12,192 M) Operating, 50,000 ft (15,240m) Non Operating		
Environment	<ul style="list-style-type: none">• ROHS, Recycling Program: https://www.xplorettech.com/about-us/environment/• Energy Star 6.1		

Zebra acquired Xplore Technologies and all its products in 2018.



NA and Corporate Headquarters
+1 800 423 0442
inquiry4@zebra.com

Asia-Pacific Headquarters
+65 6858 0722
contact.apac@zebra.com

EMEA Headquarters
zebra.com/locations
contact.emea@zebra.com

Latin America Headquarters
+1 847 955 2283
la.contactme@zebra.com